

## WHAT IS CLAIMED IS:

1           1. In a pot having a hollow body with an open end and an outlet defined in a  
2     peripheral edge defining the open end to communicate with the open end and a lid  
3     detachably mounted on the hollow body to cover the open end, wherein the  
4     improvements comprise:

5           at least one first magnet adapted to be annularly embedded in the peripheral  
6     edge defining the open end of the hollow body; and

7           two second magnets diametrically embedded in a bottom face of the lid,  
8     wherein when only one second magnet is attracted by the at least one first magnet, the  
9     lid is able to move relative to the hollow body to allow the lid to be inclined relative to  
10    the hollow body and when both second magnets are attracted by the at least one first  
11    magnet, the lid is immovable relative to the hollow body so as to close the  
12    communication between the open end and the outlet.

13          2. The pot as claimed in claim 1, wherein the hollow body has a slope formed on  
14    the peripheral edge of the hollow body and the lid has a conical bottom formed on a  
15    bottom face of the lid to correspond to the slope so that when the lid is immovable  
16    relative to the hollow body, the communication between the open end and the outlet is  
17    closed.

18          3. The pot as claimed in claim 1, wherein a first flange is formed at a joint  
19    between the slope and an inner face of the hollow body and a second flange is formed at  
20    the bottom face of the lid to correspond to the first flange such that when the lid is  
21    inclined relative to the hollow body, engagement between the first flange and the second  
22    flange enhances a connection between the lid and the hollow body.

23          4. The pot as claimed in claim 2, wherein a first flange is formed at a joint

1 between the slope and an inner face of the hollow body and a second flange is formed at  
2 the bottom face of the lid to correspond to the first flange such that when the lid is  
3 inclined relative to the hollow body, engagement between the first flange and the second  
4 flange enhances a connection between the lid and the hollow body.

5 5. The pot as claimed in claim 1, wherein there are three first magnets, two of  
6 the first magnets are diametrically arranged in the peripheral edge of the open end and  
7 the third first magnet is oppositely arranged relative to the outlet.

8 6. The pot as claimed in claim 2, wherein there are three first magnets, two of  
9 the first magnets are diametrically arranged in the peripheral edge of the open end and  
10 the third first magnet is oppositely arranged relative to the outlet.

11 7. The pot as claimed in claim 3, wherein there are three first magnets, two of  
12 the first magnets are diametrically arranged in the peripheral edge of the open end and  
13 the third first magnet is oppositely arranged relative to the outlet.

14 8. The pot as claimed in claim 4, wherein there are three first magnets, two of  
15 the first magnets are diametrically arranged in the peripheral edge of the open end and  
16 the third first magnet is oppositely arranged relative to the outlet.